VinaFlex[®] Noise Barrier Aluminum (AF) and Stainless Steel (SF) Facings

DATA SHEET

Vinaflex Aluminum (AF) and Vinaflex Stainless Steel (SF) Sheet and Rolls Vinaflex Metal Jacketing provides the blocking of unwanted sound with the durable exposed surface of aluminum or stainless steel sheet. Vinaflex is ideal for isolating piping and ducting within exposed commercial and industrial areas, as well as exterior areas requiring weather resistance.

Vinaflex[®] Mass Loaded Vinyl is permanently machine laminated to a continuous roll of aluminum jacketing (Type AF) or to a continuous roll of stainless steel jacketing (Type SF). Vinaflex Types AF and SF are available in 36" x 33-1/3' (100 sq. ft.) rolls or in cut to size 36" wide sheet.

Vinaflex Aluminum (AF) and Stainless Steel (SF) are available as combinations of any of the forms listed in the chart to the right.

Vinaflex Type AF and SF Application

Vinaflex Aluminum or Stainless Steel Jacketing should be installed over the outer surface of a sound absorbent material, such as fiberglass or mineral wool pipe covering board or blanket. The problem noise bounces off the Vinaflex barrier as it is absorbed, expending its energy within the fiberglass or mineral wool through a pin ball type travel.

Acoustical Properties

Vinaflex Type AF and Type SF laminate with 1 lb./sf Vinaflex sheet provides the following noise reduction.

Noise Transmission Loss (dB)/Frequency (Hz):								
Hz	125	250	500	1000	2000	4000	STC	
dB	20	21	23	29	34	40	29	

At one pound per square foot density the Vinaflex will provide a 29 dB noise reduction at 1,000 Hz; the noise reduction increases by approximately 5 dB for a doubling of mass/density, or for a doubling of frequency (the same effect is true for a reduction of mass/density or frequency).

For more information on GLT Products, please call toll-free at 800.874.1748 or online at www.gltproducts.com.



Innovative Insulation Systems

HEADQUARTERS:

6810 Cochran Road | Solon, OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

DISTRIBUTION CENTERS:

Ohio:	6810 Cochran Road Solon, OH 44139 440.914.1122
North Carolina:	501 West Camel Street Greensboro, NC 27401 1.800.551.9760
California:	4113 Gold River Lane Stockton, CA 95215 1.800.833.4500
Texas:	8905 Market Street Houston, TX 77029 1.800.874.1748



Vinaflex®	Metal Thickness		
Vinaflex AF ½ lb, I lb, & 2 lb/sf	.016".020", .024" & .032"		

Vinaflex SF ½ lb, .016" & .020" 1 lb, & 2 lb/sf