

SPECIFICATIONS

The Cupped Head Pin is a mild steel fabricated part made up of a weld pin and a staked-on speed clip, or retaining washer.

This product is usually applied with a capacitor discharge stud welder such as the Cutlass Pinto Stud Welder. Cupped Head pins are widely accepted as labor saving fasteners in the thermal and acoustical insulation markets.

Material: Low Carbon Steel, material specification or certification available.

Finish: Mild steel pins are galvanized coated, washer is galvanized.


Annealing: All steel pins are fully annealed unless otherwise specified.

Compatibility: All pins are compatible and recommended for use with all brands of CD stud welding equipment.



Cupped Head Weld Pin Specifications

Style	"C"	"D"	"L"
Cupped head	1½"	12 Ga. (.105)	¾" minimum
Mini-cupped head	1¾"	12 Ga. (.105)	¾" minimum



* Longer lengths are available upon request.

For more information on GLT Products, please visit us online at www.gltproducts.com or call toll-free at **1-800-874-1748**.



HEADQUARTERS:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

DISTRIBUTION CENTERS:

Ohio: 6810 Cochran Road | Solon OH 44139 | 440.914.1122

Texas: 2902 East 13th Street | Houston, TX 77571 | 713-670-9700

North Carolina: 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760

California: 4113 Gold River Lane | Stockton, CA 95215 | 1.800.833.4500